

Features

- > 17 inch Active Matrix TFT LCD Display
- > Max Resolution 1280 x 1024
- > 5-Wire Resistive Touch Screen
- > Intel Core 2 Duo / Core 2 Quad CPU
- > Up to 4GB DDR2-667 Memory
- > Up to two 2.5" SATA HDD
- > Slim CD-RW Drive
- > Detachable Computer Unit



2 x Gigabit



6x USB 2.0



1x RS-232



ARP-1717AP-108Q

Specifications	ARP-1717 AP-108Q	ARP-1717 AP-202Q	ARP-1717 AP-304Q
LCD Display			
Display Size(Diagonal)	17 inch	17 inch	17 inch
Resolution	1280 x 1024	1280 x 1024	1280 x 1024
Backlight Lifetime (Hours)	50,000	50,000	50,000
Visual Characteristics			
Colors	16 Million	16 Million	16 Million
Aspect ratio	4:3	4:3	4:3
Viewing angle (V/H)	140° / 140°	140° / 140°	140° / 140°
Response time(Typical)	12 ms	12 ms	12 ms
Pixel Pitch(mm)	0.264 x 0.264	0.264 x 0.264	0.264 x 0.264
Contrast ratio	800:1	800:1	800:1
Brightness	300 nits	300 nits	300 nits
Touch Screen			
Technology	5 Wire Resistive	5 Wire Resistive	5 Wire Resistive
Touch rating	35 Million Touches	35 Million Touches	35 Million Touches
MTBF	490,000 hours	490,000 hours	490,000 hours
Interface	RS-232	RS-232	RS-232
Driver	WinXP Pro, Win 7	WinXP Pro, Win 7	WinXP Pro, Win 7
Front Bezel			
NEMA 4	Black Powder Coated	Black Powder Coated	Black Powder Coated
NEMA 4x	Stainless Steel (Optional)	Stainless Steel (Optional)	Stainless Steel (Optional)
System			
CPU	Core 2 Duo / Core 2 Quad	Core 2 Duo / Core 2 Quad	Core 2 Duo / Core 2 Quad
Chipset	Intel Q35 + ICH9 / ICH9DO	Intel Q35 + ICH9 / ICH9DO	Intel Q35 + ICH9 / ICH9DO
Memory	Up to 4GB DDR2-667	Up to 4GB DDR2-667	Up to 4GB DDR2-667
Video Controller	Q35 Integrated GMA3100	Q35 Integrated GMA3100	Q35 Integrated GMA3100
Video Interface	VGA	VGA	VGA
Storage Option	Up to 2 x 2.5"SATA HDD	Up to 2 x 2.5"SATA HDD	Up to 2 x 2.5"SATA HDD
Compact Flash	N/A	N/A	N/A
Keyboard/Mouse	2 x PS/2 Connectors	2 x PS/2 Connectors	2 x PS/2 Connectors
Audio	Line in, Line Out, MIC-In	Line in, Line Out, MIC-In	Line in, Line Out, MIC-In
Watchdog Timer	Programmable 1 - 255 sec	Programmable 1 - 255 sec	Programmable 1 - 255 sec
Expansion Slot	1 x PCI	2 x PCI	3 x PCI
I/O Communication			
USB Port	6 x USB 2.0	6 x USB 2.0	6 x USB 2.0
Serial Port	1 x RS-232, 1 x RS-232/422/485	1 x RS-232, 1 x RS-232/422/485	1 x RS-232, 1 x RS-232/422/485
IEEE 1394	2x IEEE 1394B (optional)	2x IEEE 1394B (optional)	2x IEEE 1394B (optional)
LAN	Dual Gigabit LAN	Dual Gigabit LAN	Dual Gigabit LAN
Parallel	1 x Port	1 x Port	1 x Port
OS Support			
OS Support	WinXP Pro, Win 7	WinXP Pro, Win 7	WinXP Pro, Win 7
Power/Thermal Specs.			
Power Requirement (Max)	110VAC/3.2A,220VAC/1.6A	110VAC/3.2A,220VAC/1.6A	110VAC/3.2A,220VAC/1.6A
Power Consumption (Max)	313W	313W	313W
Heat Dissipation	1070 BTU/hr	1070 BTU/hr	1070 BTU/hr
Physical Information			
Mounting	Panel Mount	Panel Mount	Panel Mount
Net Weight	29 Lbs / 13 Kg	31 Lbs / 14 Kg	33 Lbs / 15 Kg
Physical Dimension (WxHxD)	17.80 x 13.51 x 6.07 inch 452.1 x 343.2 x 154.20 mm	17.80 x 13.51 x 6.67 inch 452.1 x 343.2 x 169.50 mm	17.80 x 13.51 x 8.30 inch 452.1 x 343.2 x 210.8 mm
Cutout Dimension (WxH)	17.13 x 12.84 inch 435.1 x 326.1 mm	17.13 x 12.84 inch 435.1 x 326.1 mm	17.13 x 12.84 inch 435.1 x 326.1 mm
Environmental			
Operating Temp	0° - 50° C (32° - 122° F)	0° - 50° C (32° - 122° F)	0° - 50° C (32° - 122° F)
Storage Temp	-20° - 60° C (-4° - 140° F)	-20° - 60° C (-4° - 140° F)	-20° - 60° C (-4° - 140° F)
Relative Humidity	5% - 95% (non-condensing)	5% - 95% (non-condensing)	5% - 95% (non-condensing)
Rating	NEMA 4/4X	NEMA 4/4X	NEMA 4/4X
Certification	N/A	N/A	N/A