

Features

- Fanless Design
- Meets IP50 rating requirements
- Supports Intel Core 2 Duo Mobile CPU
- Supports DDR2-667 Memory up to 4GB
- Dual Gigabit Ethernet
- 1 x VGA, 1 x DVI display output
- Dual field-removable 2.5" SATA HDD
- 2 x PCI expansion slots
- Built-in dual IEEE 1394B



BoxPC-238D

Specifications	BoxPC-238D	Line Drawing
System		<p>8.44 inch 214.376 mm</p> <p>5.8 inch 147.32 mm</p> <p>5.8 inch 147.32 mm</p> <p>8.44 inch 214.376 mm</p> <p>11.56 inch 293.624 mm</p> <p>1 = 2.5 HDD Bays 2 = CF Type-2 3 = KB/MS PS/2 4 = RS-232 5 = RS-232 6 = IEEE 1394b (optional) 7 = PCI 8 = VGA 9 = DVI 10 = USB 2.0 11 = RJ-45 Ethernet 12 = 24VDC Input 13 = Power Switch</p>
CPU	Core 2 Duo Mobile	
Chipset	GME965+ICH8M	
Memory	DDR2-667 up to 4GB	
Video Controller	GME965 GMA X3100	
Video Interface	VGA, DVI	
Storage Option	UP to 2 x 2.5" SATA HDD	
Compact Flash	Type II CF Slot	
Keyboard/Mouse	2 x PS / 2 connectors	
Audio	Line in, Line Out, Mic-In	
Watchdog Timer	Programmable 1 - 255 sec	
Expansion Slot	2 x PCI	
I/O Communication		
USB Port	4 x USB 2.0	
Serial Port	4 x (RS-232), 1 x (RS-232/422/485)	
IEEE 1394	2 x IEEE1394B (optional)	
LAN	Dual Gigabit LAN	
Parallel	N/A	
OS SUPPORT		
OS Support	WinXP Pro, Win 7	
Power/Thermal Specs.		
Power Requirement (Max)	24VDC / 4.6A	
Power Consumption (Max)	110 W	
Heat Dissipation	375 BTU/hr	
Physical Information		
Mounting	Wall Mount	
Net Weight	11 Lbs / 5Kg	
Physical Dimension (WxHxD)	11.56 x 5.80 x 8.00 inch 293.6 x 147.3 x 203.2 mm	
Environmental		
Operating Temp	0° - 50° C (32° - 122° F)	
Storage Temp	-20° - 60° C (-4° - 140° F)	
Relative Humidity	0% - 95% (non-condensing)	
Rating	IP50	
Certification	UL 508, CE, FCC	