


### Features

- Fanless Design
- Meets IP50 rating requirements
- Supports Intel Core 2 Duo Mobile CPU
- Supports DDR2-667 Memory up to 4GB
- Dual Gigabit Ethernet
- 1 x VGA, 1 x DVI display output
- Dual field-removable 2.5" SATA HDD
- 2 x PCI expansion slots
- Built-in dual IEEE 1394B



BoxPC-138D

Specifications	BoxPC-138D
<b>System</b>	
CPU	Core 2 Duo Mobile
Chipset	GME965+ICH8M
Memory	DDR2-667 up to 4GB
Video Controller	GME965 GMA X3100
Video Interface	VGA, DVI
Storage Option	UP to 2 x 2.5" SATA HDD
Compact Flash	Type II CF Slot
Keyboard/Mouse	2 x PS / 2 connectors
Audio	Line in, Line Out, Mic-In
Watchdog Timer	Programmable 1 - 255 sec
Expansion Slot	1 x PCI
<b>I/O Communication</b>	
USB Port	4 x USB 2.0
Serial Port	4 x (RS-232), 1 x (RS-232/422/485)
IEEE 1394	2 x IEEE1394B (optional)
LAN	Dual Gigabit LAN
Parallel	N/A
<b>OS SUPPORT</b>	
OS Support	WinXP Pro, Win 7
<b>Power/Thermal Specs.</b>	
Power Requirement ( Max )	24VDC / 4.6A
Power Consumption ( Max )	110 W
Heat Dissipation	375 BTU/hr
<b>Physical Information</b>	
Mounting	Wall Mount
Net Weight	11 Lbs / 5Kg
Physical Dimension (WxHxD)	11.56 x 3.82 x 8.00 inch 293.6 x 97.0 x 203.2 mm
<b>Environmental</b>	
Operating Temp	0° - 50° C (32° - 122° F)
Storage Temp	-20° - 60° C (-4° - 140° F)
Relative Humidity	0% - 95% (non-condensing)
Rating	IP50
Certification	CE, FCC

### Line Drawing

1 =RS-232      6 =RJ45-Ethernet  
 2 =PS2/MS Key   7 =USB2.0  
 3 =RS232      8 =Audio  
 4 =DVI      9 =LED  
 5 =VGA

- 1 ARP 1700 Series
- 2 ARP 2200 Series
- 3 ARP 3600 Series
- 4 ARP 5500 Series
- 5 AMA Series
- 6 ADM 1500 Series
- 7 ADM 1800 Series
- 8 ADM 5800 Series
- 9 ARD 1000 Series
- 10 AVW Series
- 11 BoxPC Series
- 12 Thin Clients Series
- 13 AMS Series
- 14 MPC Series
- 15 RS Series